

M10 Carriage Bolt Size & Weight Chart

M10	under-head / overall	g per piece · kg / 1000 pcs	carbon steel 7.85 g/cm³
-----	----------------------	-----------------------------	-------------------------

M10

GB/T 12-2013 · dk 21.3 · k1 6.4 · s 10.36 mm

Nominal diameter d	10 mm
Coarse pitch P (GB/T 196 series)	1.5 mm
Head diameter dk (dome max OD)	21.3 mm
Head height k1 (dome height)	6.4 mm
Square neck width s	10.36 mm
Thread length b (partly threaded basis)	26 mm

Row-level standard labelling: dimensions follow GB/T 12-2013 Round Head Square Neck Bolts (small dome head, max nominal values) as the primary source; DIN 603 is the equivalent German series and ISO 8677 the equivalent ISO series, cited for series reference only — no table values are reproduced from them. Tolerances, property classes and surface finish are agreed separately against the buyer's drawing or contract.

M10 Length Series: Under-Head / Overall / Unit Weight

Length convention (the point this chart adds): the length L specified by GB/T 12 and DIN 603 is the under-head length — measured from the bearing face (below the square neck) to the end of the shank, excluding the dome head. Overall length including the head = L + k1. Reporting the same bolt by the wrong convention shifts the figure by one head height (6.4 mm for M10), so confirm the convention with the supplier before assembly.

Under-head L (mm)	Overall L+k1 (mm)	Thread b (mm)	Unit weight (g/pc) g / piece	Bulk (kg/1,000 pcs) kg / 1000 pcs
M10×20	26.4	20	27	27
M10×25	31.4	25	30	30
M10×30	36.4	26	33	33
M10×35	41.4	26	36	36
M10×40	46.4	26	39	39
M10×45	51.4	26	42	42
M10×50	56.4	26	45	45
M10×55	61.4	26	48	48
M10×60	66.4	26	51	51
M10×70	76.4	26	57	57
M10×80	86.4	26	64	64
M10×90	96.4	26	70	70
M10×100	106.4	26	76	76
M10×120	126.4	26	88	88
M10×150	156.4	26	110	110

Unit weight = geometric volume of full-diameter shank ($\pi/4 \times d^2 \times L$) + dome head ($\pi \times h/6 \times (3r^2 + h^2)$) + square neck ($s^2 \times 0.5d$), times 7.85 g/cm3 for carbon steel; rounded to avoid false precision (whole g below 100 g, 10 g steps below 1,000 g, 100 g steps above). Length series covers the catalog standard 20-80 mm plus common longer sizes made to order.

Calculation Basis and Assumptions Disclosed

Dimensions come from fastenerCalc.CB_DIMS (GB/T 12-2013 round head square neck, max nominal values, same source as the product catalog SKUs and the online weight calculator). Unit weights are all computed from geometry x density: full-diameter shank ($\pi/4 \times d^2 \times L$) + dome head ($\pi \times h/6 \times (3r^2 + h^2)$) + square neck ($s^2 \times 0.5d$), at 7.85 g/cm3 for carbon steel, base metal only, coating excluded. Thread length follows the GB/T 12 partly threaded rule $b = 2d + 6$ (full thread when the shank is shorter, $b = L$), which matches the catalog spec_json threadLenMm row by row. No table values are reproduced from any copyrighted standard (e.g. ASME B18.5).

Boundary: unit weights are theoretical geometry estimates (excluding coatings and any rolled-thread material saving) for quotation, freight and packing budgets; actual weight varies with thread accuracy, head tolerance and coating (hot-dip galvanizing roughly +4.5%), and trade settlement is against actual measurement. Head diameter dk is a max nominal value and may differ from the buyer's drawing or sample; this chart is not an acceptance basis.

References

- GB/T 12-2013 Round Head Square Neck Bolts (National Public Service Platform for Standards Information) — https://openstd.samr.gov.cn/bzgk/gb/std?std_no=GB%2FT%2012-2013
- GB/T 196-2003 General Purpose Metric Screw Threads — Basic Dimensions, coarse pitches (same table as fastenerCalc.pitchOf) — https://openstd.samr.gov.cn/bzgk/gb/std?std_no=GB%2FT%20196-2003

- Dimensions and unit weights cross-checked row by row against carriage bolt SKU spec_json in the product catalog (same source as product pages)

Disclaimer: This table is engineering estimate data for selection, quotation and freight estimation reference only, not a design basis or acceptance standard.

Material Density Conversion

Table values are for carbon steel (7.85 g/cm3); other materials convert by density ratio: weight x factor (geometry unchanged).

Material	Density (g/cm3) g/cm³	Conversion Factor
Carbon Steel	7.85	×1.000
304 Stainless Steel	7.93	×1.010
316 Stainless Steel	7.98	×1.017
Brass	8.5	×1.083

M10 Carriage Bolt Size & Weight Chart — Yaxiio full-range reference PDF, pack v1 · generated 2026-09-10 · data source: yaxiio-customer/utlis/fastenerCalc.ts (single source of truth) · methodology matches the online tool pages · <https://www.yaxiio.com/en/tools/carriage-bolt-chart/m10>